Phoenix Multi-Fit	Input Modulation	Gal.	Height/ Diameter	Shipping Weight	
PHM130-80	35,000-130,000	80	55" / 27"	235 lbs	
PHM199-80	40,000-199,000	80	55" / 27"	235 lbs	
PHM130-100	35,000-130,000	100	63" / 27"	405 lbs	
PHM199-100	40,000-199,000	100	63" / 27"	405 lbs	

Direct Gas Fired Water Heaters

## **Phoenix Multi-Fit**



- Up to 96% thermal efficiency
- Up to 5 to 1 turndown ratio
- Built-in auxiliary taps provide connections to air handlers or storage tanks
- Industry 1st for condensing water heaters: both top & side connection (inlet & outlet)
- Robust 316L stainless steel tank
- Extremely lightweight tank fits virtually anywhere; 63" height
- Beautiful stainless steel look



## Phoenix Solar

Sunshine Is Free, Why Not Use It To Heat Your Water

 Eligible for tax credits and utility company rebates

 7 year residential / 3 year commercial limited warranty

Phoenix Solar Model	Input Modulation	Gal.	First Hr. Rating	Height/ Diameter	Shipping Weight
PH130-80S	35,000-130,000	80	227 gal	72" / 23"	245 lbs
PH130-119S*	35,000-130,000	119	257 gal	74" / 27"	245 lbs
PH199-80S	35,000-130,000	80	314 gal	72" / 23"	415 lbs
PH199-119S*	35,000-130,000	119	335 gal	74" / 27"	415 lbs

\*SNHX (Solar No Heat Exchanger) Versions Available



## Stainless Steel Indoor/Outdoor Gas Fired Water Heater

- 2 hybrid cupronickel/stainless steel heat exchangers (built-in redundancy)\*
- Up to 95% thermal efficiency
- Up to 10:1 turndown ratio\*
- No anode rods needed
- Best 1st hour output and recovery
- Load-matching modulation
- Low NOx combustion system meets
- 119 gallon storage: reduced cycling adds to component life, No additional storage tanks needed
- Spark ignition system
- Limited warranty: 3 year commercial (upgradable to 5 year)

## High Efficiency

Phoenix Plus	Btuh/Hr Input Modulation	Approx. Shipping Weight	GPH at 100°F Rise	First Hour Rating	Gal.
PHP199-119*	40k–199k Btuh	475 lbs.	232	315 gal.	
PHP260-119	35k–260k Btuh	555 lbs.	303	386 gal.	119
PHP320-119	40k-320k Btuh	575 lbs.	372	455 gal.	
PHP399-119	40k–399k Btuh	575 lbs.	464	574 gal.	

\*The 199K model does not have dual combustion system and does not have built-in redundancy (5:1 Turndown)

