

American Standard®

WATER HEATERS

Commercial Line

MODEL: 75-76-AS

75 GALLON LIGHT DUTY STORAGE

76,100 BTU NAT GAS

76,100 BTU L.P. GAS

75-76-AS Features

The American Standard Commercial Gas Model 75-76-AS is designed to fulfill the hot water requirements of large residences, small restaurants, businesses, barber and beauty shops, small office buildings and multi-family developments up to four single or three double bath units.

- **Heavy Gauge Steel Tank** – for extra years of trouble-free service.
- **Inner Tank Glass-Lined** – with Dura-Glas™ and fired at 1600° F for optimum protection from the effects of corrosion.
- **R-16.7 Non-CFC Foam Insulated** – to save energy and reduce fuel costs by maximizing heat retention.
- **Two Anode Rods** – to prolong tank life.
- **Self-Cleaning Turbulence Inducing Cold Water Inlet-Tube** – engineered to diminish hard water area sediment deposits.
- **Full Sized Hand-hole Cleanout** – for eased tank inspection and/or removal of sediment deposits.
- **Furnished with Four Heavy Gauge Steel Legs** – designed to maximize durability & afford rock-steady installation.
- **Automatic Non-Electric Gas Thermostat Adjustable to 180° F** – When installed with a mixing valve, the 75-76-AS can deliver 180° F sanitizing & 140° F general purpose hot water simultaneously.
- **Combustion Chamber Door** – including hinged knob outside access & sliding inner door to sequester burner & pilot area for added safety.
- **Factory Installed Energy Cut-Off System & Pressure/Temperature Relief Valve.**
- **Small Vent Size & Top Mount 1 1/2" Water Connections** – to afford universal replacement of other brands.
- **AMERICAN STANDARD Gas Water Heaters** – are certified at 300 PSI test pressure & for 150 PSI working pressure.
- **All Tanks Are Hydrostatically Tested at the Factory.**
- **Tested & Listed with CSA International** – in accordance with ANSI Z21.10.3 - CSA 4.3 for up to 180° F operation as an automatic storage and/or automatic circulating tank heater. ASHRAE Standard 90.1 1999 addendum 90.1b. CSA certified to meet NSF/ANSI 5 Standards.
- **Three Year Limited Warranty** – on inner glass-lined tank and one year limited warranty on all other component parts.




THIS WATER HEATER MEETS THE REQUIREMENTS
OF ASHRAE AND MEETS OR EXCEEDS THE
THERMAL EFFICIENCY REQUIREMENTS
OF CALIFORNIA AND OTHER STATES RECOGNIZING ASHRAE.

American Standard

WATER HEATERS

561 New York Drive, Pomona, California 91768
(800) 900-9063 * (909) 392-0230 * FAX (909) 392-7302

75-76-AS SPECIFICATIONS AND APPLICATION DATA



SPECIFICATIONS

MODEL NUMBER	TANK GALLONS CAPACITY	BTU INPUT NAT GAS	REC GPH 100° RISE	BTU INPUT L.P. GAS	REC GPH 100° RISE	THERM EFF %
75-76-AS	75	76,100	74	76,100	74	80%

*For Propane (LP) Gas Model add suffix "LP"; For SCAQMD Low NOx Model add prefix "N"

DIMENSIONS SHOWN IN INCHES

EXTERIOR DIMENSIONS			VENT	TOP WATER PIPE SIZE	WATER I.P.S. CONNECTIONS		GAS I.P.S. CONN.		HGT TO T&P OPENING	T&P OPENING
A	B	C			HEIGHT TO TOP CONNECT	TOP WATER SPREAD	HGT	SIZE		
67 ^{3/8}	26 ^{1/4}	63 ^{1/2}	4	1 ^{1/2}	68 ^{1/2}	16	18	1/2	56 ^{1/2}	3/4

RECOVERY IN GALLONS PER HOUR AT VARIOUS TEMPERATURE RISES

MODEL NUMBER	GAS TYPE	BTU INPUT	TEMPERATURE RISE										
			40°	50°	60°	70°	80°	90°	100°	110°	120°	130°	140°
75-76-AS	NAT	76,100	185	148	123	105	92	82	74	67	62	57	53
	LP	76,100	185	148	123	105	92	82	74	67	62	57	53

MAXIMUM HOT WATER DELIVERABILITY AT VARIOUS TIME PERIODS

STORAGE CAPACITY U.S. GALLONS	ONE HOUR RECOVERY 100° RISE	1 ST HOUR	2 HOURS	3 HOURS	GPM REC. 100° RISE
75	74	127	201	275	1.2

Note: Recovery rate indicated on heater rating plate is based on 75% (76%) thermal efficiency according to CSA (ANSI, Z.21.10.3) Manufacturer reserves the right to make product changes and/or improvements with or without notice.

SAMPLE SPECIFICATION

Commercial gas water heater shall be AMERICAN STANDARD model _____ having a storage capacity of _____ gallons, operate on _____ Gas, with a BTU input of _____ and a recovery rate of _____ gallons per hour at 100° F temperature rise. Water heater tank interior shall be glass lined with Dura-Glas™, furnished with four anode rods and insulation shall be non-CFC foam of R-16.7. Water heater shall be CSA certified.



American Standard
WATER HEATERS

561 New York Drive, Pomona, California 91768
1(800) 900-9063 • (909) 392-0230 • Fax (909) 392-7302